

## QUESTIONS AND ANSWERS PERTAINING TO THE CONTRACT NOTICE 5/T/2024

### *Supply of agricultural machinery and equipment and delivery of related ancillary services in Libya*

**Date:** 27.06.2024

N°	DATE	QUESTION	ANSWER
1	21.06.2024	With regard to the seed hopper, technical specifications indicate “not less than 500 kg”. Could you please confirm if the seed hopper must indeed have a capacity of at least 500 kg?	Yes, correct. The seed hopper must have a capacity of not less than 500 kg.
2	24.06.2024	The draft contract in the tender dossier is made based on the general conditions of contract contained in the same dossier. Are there any specific conditions foreseen to be applied to once the tender has been awarded?	Yes, confirmed. As specified in Art. 5 of the draft contract, specific conditions might apply with regard to the execution of the contract by the successful tenderer.
3	25.06.2024	Item No. 10 “Potato rotary Bed former” and No. 12 “Potato haulm topper” seem to have the same specifications. Please clarify.	<p>The machines detailed in item n.10 and in item n. 12 are different from each other.</p> <p>The machine in item No. 10 refers to the rotary tillers used to shape two windrows for the subsequent sowing of the potato.</p> <p>The machine in item No. 12 refers to the knives rotary machine for shredding leaves to be used before the potato digger.</p>

			Both machines will operate on two parallel rows spaced in the range 0.8-0.9m apart.
4	25.06.2024	<p>With regard to item No. 4 “Medium power tractor”:</p> <ol style="list-style-type: none"> <li>1. please confirm that 2 double acting rear hydraulic remote valves will be accepted;</li> <li>2. please confirm that tires size 420/85R38 will be accepted;</li> <li>3. please confirm that 3400Kg will be accepted whereas lifting weight of 4500KG is too high for 110HP tractors without cabin.</li> </ol>	<p>With regard to item No. 4 - Medium power tractor:</p> <ol style="list-style-type: none"> <li>1. Offers with a number of double acting rear hydraulic remote valves less than 4, will not be accepted.</li> <li>2. Yes, tires size 420/85R38 can be accepted.</li> <li>3. The question seems rather unclear. Actually, it is not clear if 4500 kg refers to the capacity of the rear lift or to the weight of the tractor.</li> </ol> <p>However, as reported in the technical specifications for tractor Item No. 4, the following specifications are required:</p> <ul style="list-style-type: none"> <li>• Max. lift capacity at ball ends: not less than 3500 kg.</li> <li>• Weight of the tractor without additional ballast or water in wheels, and empty tanks: Not less than 4500 kg.</li> </ul>